



A colorfast cementitious grouting known as **New Dubai Tile Grout** is used as a jointer for the majority of ceramic tile and natural stone applications. Dubai Tile Grout has applications both inside and outside the home. For use in dry regions, Dubai Tile Grout is the best grout to use.

ADVANTAGES

- Eliminates mold.
- A strong adherence.
- Tiles are not stained.
- Outstanding resistance to UV.
- Available in a variety of hues.
- Not prone to cracking.
- Once applied, there is no need for sealing.

SURFACE PREPARATION

Check to see if the tile glue has completely dried before beginning the grouting. Using **New Dubai Tile Grout** with the suggested tile adhesive. In most cases, the tile adhesive needs 24 hours to dry. From the grout joints, take out any spacers, lugs, extra adhesive, and loose foreign objects. To ensure proper adhesion, the joints must be free of debris, pollution, and other impurities. By adding clean, potable water, the background suction should be neutralized. In order to prevent de-bonding, there should be no free water in the joints that will be grouted.

PRODUCT PREPARATION

To create a lump-free toothpaste consistency, gradually add the **New Dubai Tile Grout** powder to a clean pail of premeasured clean water while stirring continuously. To prevent the powder from settling at the bottom of the mixing container, it should be added above the water. The mixing container needs to be clean, non-corrosive, and uncontaminated. Use only potable water when blending. To ensure a consistent, lump-free mix, it is also advised that the material be mechanically combined using a mortar and pestle or other mechanical mixing techniques.

APPLICATION

Using a rubber spatula, apply **Dubai Tile Grout** to the tile joints, taking care to press the grout firmly into the spaces between the tiles. Use a dry cloth or sponge to remove any extra material from the tile's surface. The remaining grout can be cleaned with a wet sponge. frequently clean the sponge.



Plot # MB-83 Mehran Town, Korangi Industrial Area Karachi, Pakistan



www.newdubaibond.com



(+92) 314 9689443



TECHNICAL DATA

Appearance	White, gray, or colored powder
Composition	contains cement, specific aggregates, and colors and additives to, increase consistency, workability, and durability.
Maximum aggregate size	0.3mm
*Water application	36% ± 5%
*Wet Mix life	Tested as per BS EN 1015-9 Approximately < 30 Minutes @ 20°C
*Approximate Yield / Coverage	0.85 m ³ / T

PACKAGING

New Dubai Tile Grout is available in the following packaging:

Dubai Tile Grout is available in the following packaging.

1 KG pouches & 1 KG Jar.

10 KG Bags Supplied as individual bags.

SHELF LIFE

New Dubai Tile Grout has a 12-month shelf life when kept in dry, protected conditions.

HEALTH & SAFETY

New Dubai Tile Grout is thought to be safe for shipment. Avoid reusing bags or containers, and dispose of them in accordance with local laws. During application, gloves and the appropriate masks can be worn. For more details on the product's health and safety, please consult the MSDS.



Plot # MB-83 Mehran Town, Korangi Industrial Area Karachi, Pakistan



www.newdubaibond.com



(+92) 314 9689443